

FSK[™] Belt Skiver

Quickly and Easily Remove Belt Top Cover to Recess Mechanical Fasteners

Whenever possible, Flexco recommends skiving the belt in order to countersink mechanical fasteners. Skiving reduces the fastener profile on the belt, resulting in improved fastener/cleaner compatibility and increased fastener service life.



Safe, On-Site Operation

Portable, lightweight, and easy to carry, the FSK™ Belt Skiver adjusts easily to the precise cutting depth you need. The blade is safely enclosed during skiving operations. The FSK is compact, so it is easy to use anywhere on the job site – even in cramped operating environments.

Used on rubber-covered belts with top covers of 3/16" (4.5 mm) or more, the FSK Skiver provides skives from 1/16" to 3/8" (1.5 to 9.5 mm) deep in a single pass. Deeper skives can be achieved with multiple passes. The FSK can also be used on most worn or damaged belt surfaces.





Features and Benefits



Easily select and set the depth of the skive.



Front drive rollers aggressively grip belt at the start of the skive to prevent slippage.



Easily adjust the fence for the appropriate fastener size.

FSK[™] Belt Skiver

A Safer Way to Skive a Belt

The FSK[™] Belt Skiver safely removes top cover for installation of recessed splices.

• Blade safely enclosed during skiving operations

• Portable and lightweight

• Ideal for rubber-covered belts with top covers 3/16" (4.5 mm) thick or more

• Skives belts between 1/4" (6.5 mm) and 1-1/4" (32 mm) thick



Ordering Information	
Description	Ordering Number
Skiver Complete with Standard Blade	FSK2
Sharpening Stone	31987
REPLACEMENT PARTS	
Skiver Blade-Standard	FSK-1B
Skiver Blade-High Wear	FSK-1BA
Skiver Ratchet Assembly	FSK-1R
Skiver Fence Assembly	FSK2-F
Replacement Drive Rollers-Set of 10	FSK2-DR

ISO 9000

Authorized Distributor:

2525 Wisconsin Avenue • Downers Grove, IL 60515-4200 • USA Tel: (630) 971-0150 • Fax: (630) 971-1180 • E-mail: info@flexco.com

